



SPECIFICATIONS

Expandable	Tracks
Swing	Boom
Operating Weight:	1000 kg
Digging Bucket Capacity:	0.025 cbm
Bucket Width:	380 mm
Engine:	Koop Diesel Euro 5
Rated Power:	8.6 kW / 3600 rpm
Main Pump:	Wanye Hydraulic
Hydraulic Pressure:	16 MPa
Swing Motor:	Dali
Travel Motor:	Dali
Travel Speed:	1.5 km/h

Undercarriage Width:	896 mm
Track Width:	200 mm
Ground Clearance (Undercarriage):	132 mm
Track Height:	320 mm

WORKING RANGE

Maximum Digging Depth:	1650 mm
Maximum Digging Height:	2610 mm
Maximum Dumping Height:	1850 mm
Maximum Digging Radius at Ground Level:	2890 mm
Swing Radius:	360°
Maximum Dozer Blade Lift Height:	345 mm
Maximum Dozer Blade Digging Depth:	255 mm

MAIN DIMENSIONS

Length:	2770 mm
Width:	930 mm
Height:	2100 mm
Overall Track Length:	1230 mm



200 mm Bucket




500 mm Bucket



800 mm Bucket



Earth auger



Hydraulic breaker



Quick coupler



Rake



Ripper tooth



Wood grapple

