



■ SPECIFICATIONS

Machine Weight:	800 kg
Engine Model:	Briggs & Stratton
Number of Cylinders:	2
Cooling Method:	Air-cooled
Drive:	Gasoline
Maximum Height:	2400 mm
Minimum Height:	1270 mm
Bucket Capacity:	0.15 m³
Bucket Load Capacity:	400 kg
Nominal Pressure:	18 MPa
Hydraulic Pump:	Parker
Hydraulic Pump Flow Rate (L/min):	15+15+15
Engine Displacement for Walking Mechanism:	BM5-375 ml
Distributor:	Italy M45
Rated Power:	17 kW
Engine Oil Capacity:	1.7 L
Tire Specifications:	18*8.50-8
Hydraulic Oil Tank Capacity:	25 L
Fuel Tank Capacity:	20 L





Width:	1150 mm
Height:	1300 mm
Bucket Width:	1150 mm
Wheelbase:	640 mm
Ground Clearance:	100 mm
Maximum Slope for Operation:	25%

■ OPERATING RANGE

Maximum Loading Height:	2080 mm
Maximum Unloading Height:	1950 mm
Rated Speed:	3200 r/min

■ MAIN DIMENSIONS

Length:	230 mm
---------	--------

 Sweeper	 4-in-1 bucket
 Chain trencher	 Forks bucket
 Bucket with grapple	 Grading scraper
 Pallet fork	

