



■ SPECIFICATION

Rated Load Capacity:	850 kg
Weight:	1860 kg
Engine:	Kubota Euro 5
Cooling System:	Water cooling
Number of Cylinders:	4
Rated Power:	18.2 kW
RPM:	2600
Pressure:	190 bar
Hydraulic Oil Flow - Working:	67 L/min
Hydraulic Oil Flow - Drive Pump:	78 L/min
Fuel Tank Capacity:	23 L
Battery Capacity:	60 Ah
Voltage:	12 V

■ WORKING RANGE

Travel Speed:	12 km/h
Steering Angle:	45°

Standard Tire:	26X12-12
Tire Pressure:	2.8 Bar
Maximum Lifting Height:	3 m (3000 mm)
Bucket Tilt Angle from Horizontal (Maximum Opening):	30°
Maximum Reach (Boom Retracted):	2480 mm
Machine Ground Clearance:	1050 mm

■ MAIN DIMENSIONS

Overall Machine Length:	2600 mm
Overall Machine Width:	1240 mm
Overall Machine Height:	2130 mm
Overall Height with Boom Fully Raised and Bucket Open:	3430 mm
Distance from Front Wheels to Front of Bucket (Full Extension):	1520 mm
Wheelbase (Front to Rear Axle):	1350 mm
Distance from Rear Axle Center to Rear of Machine:	850 mm
Distance from Rear Axle Center to Front of Machine (Without Extended	

