



SPECIFICATION

Operating weight:	2560 kg
Nominal load capacity:	900 kg
Exhaust emission standard:	Euro 5
Engine:	Kubota V1505
Nominal power:	18.2 kW / 2300 rpm
Maximum torque:	92.6 / 1700 rpm
Displacement:	1.498 l
Number of cylinders:	4
Drive type:	Hydrostatic
Axle:	K80B
Maximum pressure in the hydrostatic drive system (optional):	310 bar
Hydraulic working system efficiency (maximum) / (optional):	41.4 (50.4) / 32-64 (39-78) l/min
Maximum pressure in the working hydraulic system (optional):	180 bar
Quick coupling system (optional):	Hydraulic

WORKING RANGE

Travel speed:	12 km/h
Bucket capacity:	0.4 m³
Steering angle to each side:	42°
Rear departure angle:	20.75°
Turning radius with bucket in transport position:	3330 mm
Turning radius at outer edge of tire:	2796 mm
Bucket width:	1650 mm
Bucket tilt angle at transport position:	35°
Bucket tilt angle at maximum height:	55°

Maximum discharge angle at maximum height:	32°
--	-----

MAIN DIMENSIONS

Length:	4513 mm
Width:	1451 mm
Height:	2254 mm
Wheelbase:	1595 mm
Ground clearance:	351 mm
Discharge clearance at maximum height:	2759 mm
Discharge reach at maximum height:	1371 mm
Maximum lifting height:	3448 mm

4-in-1 Bucket	Auger
Bale Grab	Grapple (Crocodile-type)
Mower	Pallet Forks
Snow Plow	Sweeper

