



SPECIFICATION

Engine:	Perkins EURO 5
Engine Type:	Inline, water-cooled, three-cylinder diesel engine
Nominal Power:	18.4 kW
RPM:	2200 rpm
Fuel Consumption (standard conditions):	≤230 g/kW.h
Weight:	2800 kg
Max. Travel Speed:	18 km/h
Drive:	Hydraulic motor, four-wheel drive
Drive Pump:	PWG
Working Pump:	Zaneda
Steering System:	Rear axle with hydraulic assistance
Drive System:	35 MPa; 46 cc
Working System:	24 MPa; 22 L/min
Parking Brakes:	Electric parking brake
Working Brakes:	Hydraulic oil cut-off brake
Quick Coupler System:	Yes
Joystick:	Yes
Self-Leveling:	Yes

WORKING RANGE

Bucket Capacity:	0.3 m³
Bucket Width:	1588 mm
Load Capacity:	1200 kg
Tire Model:	26*12-16.5
Tire Width:	275 mm

Tire Diameter:	658 mm
Minimum Turning Radius:	3560 mm
Wheelbase:	1720 mm
Track Width:	1150 mm

MAIN DIMENSIONS

Overall Length (bucket on the ground):	3350 mm
Overall Height:	1955 mm
Overall Width:	1588 mm
Max. Lifting Height:	4010 mm

Silage fork

Bale Grab

Sweeper

4-in-1 Bucket

Snow Blade

